

## **Photo Requirements**

For Heating Rebates in Single Family Homes

## **Heat Pumps**

Nameplates for indoor and outdoor installed equipment (outdoor unit, air handler, indoor units)



OF LIT STOTEM HEAT PUMP <H CERTIFIED CONFORMS TO ANSIUL STD. 1995 CERTIFIED TO CANICSA STD C22.2 NO.238 MXZ-3C24NA2 SERVICE REF. MXZ-3C24NA2-U1 MAX.VOLTAGE 253 UNIT SUPPLY 200/230 1 60 MIN. VOLTAGE 198
APPROVED FOR HACR BREAKERS OR TIME DELAY FUSES. MAX FUSE 25 AMPS MIN.CIRCUIT AMPACITY 22.1 FAN MOTOR COMPRESSOR SCCR 5 KA REFRIGERANT R410A FACTORY CHARGED 6 LBS 13 OZ

IF THE LIQUID LINE EXCEEDS 98.4 FT., PLUS 1.08 OZ

PER ADDITIONAL 5FT. LIQUID LINE

INSTALLER TO MARK TOTAL CHARGE LBS OZ DESIGN PRESSURES PSIG 601 HI SIDE 320 LO SIDE \* SUITABLE FOR OUTDOOR INSTALLATION WEIGHT 137 LBS. SERIAL NO. OYUS3140A MITSUBISHI ELECTRIC CORPORATION

Installed air handler showing filter (and condensate pump if applicable)

Installed Air Handler



Installed outdoor unit





## **Photo Requirements**

For Heating Rebates in Single Family Homes

Filter grill(s) showing installed filter size and MERV rating (if applicable)





Condensate Drain - OD condensate termination



[If Mitsubishi] Auxiliary Lockout Controller located on air handler






## **Photo Requirements**

For Heating Rebates in Single Family Homes

Air Source thermostat showing outdoor temperature and auxiliary lock out control screen.





Duct sealing and insulation [Need PRE and POST condition photos]

Pre-insulation locations of sealed ducts. (Dovetails, Elbows, Ys)





Two or three locations of insulated ducts wrapped with twine.

